

150LB

Size	L	H1	H2	H3	H4	H5	D0	ISO 5211
2"	43	125	105	65	11	34	250	F07
2.5"	46	135	120	65	11	34	250	F07
3"	48	145	120	70	13	34	250	F07
4"	54	155	140	70/90	13	34	250	F07/F10
5"	57	185	150	90	16	34	250	F10
6"	57	190	165	90	16	41	320	F10
8"	64	245	235	90	19	41	320	F12
10"	71	300	265	95	19	54	360	F12
12"	81	340	325	110	20	54	460	F14
14"	92	350	330	110	20	59	600	F16
16"	102	375	375	110	21	59	600	F16
18"	114	395	375	110	22	59	600	F16
20"	127	450	420	125/125	24	61	600	F16/F25
22"	154	450	450	125	24	61	600	F25
24"	154	490	495	125	25	61	600	F25
26" A	165	505	510	125/155	25	61	600	F25/F30
26" B	165	470	475	125/155	25	61	600	F25/F30
28" A	165	555	565	180	26	61	600	F30
28" B	165	510	505	180	26	61	600	F30
30" A	190	630	595	180	26	69	600	F30
30" B	190	560	570	180	26	69	600	F30
32" A	190	635	630	180/180	26	69	600	F30/F35
32" B	190	580	570	180/180	26	69	600	F30/F35
34" A	203	665	660	180	30	69	600	F35
34" B	203	605	605	180	30	69	600	F35
36" A	203	735	685	180	30	127	650	F35
36" B	203	625	635	180	30	127	650	F35
38" A	216	765	735	180	30	153	700	F35/F40
38" B	216	700	660	180	30	153	700	F35/F40
40" A	216	700	755	180	30	153	700	F40
40" B	216	685	685	180	30	153	700	F40
42" A	254	780	800	180	30	153	700	F40
42" B	254	730	715	180	30	153	700	F40
44" A	254	800	825	200	32	153	700	F40
44" B	254	745	750	200	32	153	700	F40
48" A	254	865	860	200	33	193	750	F40
48" B	254	780	805	200	33	193	750	F40
52" A	390	935	960	210/230	33	193	750	F40/F48
52" B	390	845	855	210/230	33	193	750	F40/F48
56" A	390	975	985	230	38	208	750	F48
56" B	390	900	915	230	38	208	750	F48
60" A	390	1060	1050	230	40	208	750	F48
60" B	390	965	975	230	40	208	750	F48

300LB

Size	L	H1	H2	H3	H4	H5	D0	ISO 5211
2"	43	135	105	70	13	34	250	F07
2.5"	46	140	125	70	13	34	250	F07
3"	48	155	130	70/90	16	34	250	F07/F10
4"	54	185	165	90	16	41	320	F10
5"	59	200	170	90	16	41	320	F10
6"	59	230	210	95	19	54	360	F12
8"	73	260	245	100	20	54	460	F14
10"	83	300	290	110	20	59	600	F16
12"	92	345	330	110	21	59	600	F16
14"	117	375	370	110	22	61	600	F25
16"	133	390	395	125	24	61	600	F25
18"	149	430	425	125/135	24	69	600	F25/F30
20"	159	465	460	125/135	26	69	600	F25/F30
22"	181	510	495	125/135	26	76	600	F25/F30
24"	181	535	530	135	26	127	650	F35
26" A	210	580	570	180	28	127	650	F35
26" B	210	550	545	180	28	127	650	F35
28" A	229	560	570	180/210	30	127	650	F35/F40
28" B	229	515	510	180/210	30	127	650	F35/F40
30" A	241	630	615	210	30	127	650	F40
30" B	241	590	595	210	30	127	650	F40
32" A	241	670	650	210	36	193	750	F40
32" B	241	620	605	210	36	193	750	F40
34" A	241	710	690	230	36	193	750	F48
34" B	241	660	650	230	36	193	750	F48
36" A	241	735	725	230	36	193	750	F48
36" B	241	705	690	230	36	193	750	F48
38" A	300	690	680	230	38	208	750	F48
38" B	300	720	705	230	38	208	750	F48
40" A	300	720	715	230	38	208	750	F48
40" B	300	730	720	230	38	208	750	F48
42" A	300	745	735	230/260	38	208	750	F48/F60
42" B	300	755	735	230/260	38	208	750	F48/F60
44" A	360	750	740	230/260	38	208	750	F48/F60
44" B	360	770	765	230/260	38	208	750	F48/F60
48" A	360	850	840	230/260	38	250	800	F48/F60
48" B	360	865	860	230/260	38	250	800	F48/F60
52" A	390	900	890	260	40	250	800	F60
52" B	390	915	910	260	40	250	800	F60
56" A	390	960	955	260	40	250	800	F60
56" B	390	985	980	260	40	250	800	F60
60" A	440	1015	1010	260	40	250	800	F60
60" B	440	1040	1030	260	40	250	800	F60

600LB

Size	L	L (RTJ)	H1	H2	H3	H4	H5	D0	ISO 5211
3"	54	54	185	200	95	16	41	320	F12
4"	64	64	195	205	95	16	41	320	F12
5"	78	78	235	240	95	16	59	600	F14
6"	78	78	250	250	95	16	59	600	F14
8"	102	102	290	295	125	22	59	600	F16
10"	117	117	350	340	125	22	61	600	F25
12"	140	140	390	380	125/135	24	69	600	F25/F30
14"	155	155	405	385	125/135	24	69	600	F25/F30
16"	178	178	450	440	160	24	69	600	F35
18"	200	200	530	510	160	24	127	650	F35
20"	216	216	520	505	180/210	30	153	700	F35/F40
24"	232	232	595	570	210	32	193	750	F40
26" A	292	292	595	580	210/230	38	208	800	F40/F48
26" B	292	292	565	555	210/230	38	208	800	F40/F48
28" A	292	292	690	670	230	38	208	800	F48
28" B	292	292	570	565	230	38	208	800	F48
30" A	318	318	650	665	230	38	208	800	F48
30" B	318	318	605	595	230	38	208	800	F48
32" A	318	318	705	635	260	40	250	800	F60
32" B	318	318	665	605	260	40	250	800	F60
36" A	330	330	760	715	260	40	250	800	F60
36" B	330	330	660	675	260	40	250	800	F60
40" A	410	410	790	760	260	40	250	800	F60
40" B	410	410	725	685	260	40	250	800	F60

900LB

Size	L	L (RTJ)	H1	H2	H3	H4	H5	D0	ISO 5211
6"	210	210	275	270	125	22	59	600	F16
8"	230	230	320	315	125	22	61	600	F25
10"	250	250	375	365	125	22	61	600	F25
12"	270	270	415	400	135	24	76	600	F30
14"	290	290	435	420	160	24	127	650	F35
16"	310	310	480	455	160	24	153	700	F40
18"	330	330	560	505	180	35	153	700	F40
20"	350	350	570	535	180	35	153	700	F40
24"	390	390	645	620	200	40	208	750	F48

1500LB

Size	L	L (RTJ)	H1	H2	H3	H4	H5	D0	ISO 5211
6"	210	210	305	295	135	24	61	600	F30
8"	230	230	355	345	135	24	61	600	F30
10"	250	250	440	400	160	28	69	600	F35
12"	270	270	500	460	180	28	127	650	F40
14"	290	290	535	500	200	40	153	700	F48
16"	310	310	575	540	200	40	153	700	F48
18"	330	330	620	625	200	40	153	700	F48
20"	350	350	655	660	240	55	208	750	F60
24"	390	390	750	756	240	55	208	750	F60

SPECIFICATION 制造标准 :

Design Code 设计标准:

API 609 Catalog B & ASME B16.34

Face to face 结构长度

API 609 Category B, BS 5155

ISO 5752 & BS EN 558 Series 20 / 14 / 16

Connection Standard 连接标准

NPS 2"~24" ASME B16.5

Above 24" ASME B16.47 A / B

Testing / Inspection 试验与检验

API 598

